

Produktblad **sE Electronics V-BEAT**

sE Electronics V-BEAT Snare / Tom mic - Effortless sonics, superior isolation, minimal footprint.

Effortlessly amazing sound for any snare or tom

The V BEAT is the most compact drum microphone in its class, intended for use with snare or tom drums.

Unlike the V7, which is optimized for vocals, the V BEAT features the same high-grade sonic performance as the V7 X instrument dynamic, but in a dedicated low-profile & drum-friendly form factor. Tuned for instrumental use, it can also be used on sources such as electric guitar speaker cabinets or brass instruments. Its specialized capsule provides a highly detailed, extremely natural sound character on snares or toms of any size, with amazing off-axis rejection to minimize bleed from nearby drums and cymbals. Its ultra-compact design and parallel XLR connector & stand mount give it the smallest footprint in its class, and its rock-solid swivel mount allows its angle to be adjusted with great precision – so it can be aimed at almost any part of the drum head to achieve whatever sound character is required. Compact, flexible, and minimalist design The V BEAT utilizes an extremely low-profile mechanical design, with the XLR connector and stand mount integrated in parallel on the underside of the flexible swivel mount. This minimizes the V BEAT's footprint, removes any cables from line-of-sight, and negates the need for any right-angle adapters or special cables. It also means there's no danger of cables interfering with the drummer's performance, as they are kept out of the way of cymbals and drum sticks alike. When used as intended with the V CLAMP, the V BEAT becomes even more compact and even more flexible. The V CLAMP adds another axis of vertical movement for even better fine-positioning ability, and keeps the V BEAT securely fastened to your drum rim while adding barely any bulk to the overall footprint. The heart of the V BEAT: the DMC7 X capsule The custom DMC7 X capsule offers the same technologies and features as its sibling within the acclaimed V7, including the innovative, specialized aluminum voice coil. While the V7 is optimized for vocals, the capsule in the V BEAT has been custom-tuned for instrumental use. With aluminum being a much lighter material than the industry standard (copper), it delivers an open and transient-rich sound, with deep and clear lows for stellar performance. The midrange is also extremely balanced, supporting the natural resonances of percussive instruments. The excellent off-axis rejection of this sophisticated capsule also helps isolate your drums from other sound sources on the stage - efficiently reducing stage bleed and spill from other drums, cymbals and more. The supercardioid pattern also allows you to easily tailor the bottom-end by adjusting the proximity effect – i.e. distance to the drum head. Proven Neodymium magnets, tight production tolerances and high workmanship ensure excellent



sensitivity, high-end sound quality and superb consistency. Unique, patented integrated capsule suspension The V BEAT™s advanced internal capsule suspension efficiently decouples the capsule from mechanical vibration, isolating it from shocks & jolts and eliminating the need for an external shock mount. All-metal housing & spring steel grille with gold XLR connector The V BEAT™s road-ready chassis is all metal, with no fragile plastic parts. The chassis' high quality, highly durable die-cast zinc alloy is designed to hold up under on-stage stress for years, the spring steel mesh grille is dent-proof and corrosion-free for perfect reliability, and the tightening knob for the swivel mount maintains a rock-solid hold on the V BEAT in any position. Plus, the V BEAT™s gold-plated XLR connector ensures a loss-free and reliable signal connection for years to come. Internal windscreen The red internal windscreen efficiently reduces unwanted popping, plosives and wind noise -and in case you prefer a more visually subtle black windscreen, we have also included one as a standard accessory. IN THE BOX thread adapter zipper pouch spare black internal windscreen sE logo sticker user manual knurled nut for 3rd part accessories

SPECIFICATIONS Capsule: Dynamic Voice Coil: Aluminum Magnet: Neodymium Directional Pattern: Supercardioid Frequency range: 30 Hz - 19 kHz Impedance: 300 Ohms Sensitivity: 2.0 mV/Pa (-54 dBV) Connectivity: 3-pin male XLR Height: 61 mm (2.4 in.) x Length: 110 mm (4.3 in.) Weight: 347 g **V CLAMP SPECIFICATIONS** Height: 75 mm x Length: 57 mm Weight: 93 g

XL1315730 sE Electronics V-BEAT 2250 kr inklusive moms

Lagerstatus: Ungefär 5 dagar