

Produktblad Celestion CDX1-1070 T5916 8R

Celestion CDX1-1070 T5916 8R 16" exit light weight, low-profile ferrite magnet compression driver

Celestion Compression Drivers HF Celestions

kompressionsdrivers är tillverkade med den allra senaste datortekniken för att leverera den perfekta balansen av prestanda, verkningsgrad och vikt. FEA teknik har används för att undersöka beteendet hos ljudvågorna inom kompressionsdrivern. Med denna information kan varje enskild driver anpassas så att en korrekt vågform alltid avges efter komprimering.

- Power rating: 20W RMS
- Nominal impedance: 8ohm
- Frequency range: 1500-20,000Hz
- Sensitivity: 106dB
- Recommended min. crossover: 2200Hz (12dB/oct)
- Voice coil diameter: 25mm/1in
- Voice coil material: Copper clad aluminium
- Diaphragm material: PETP film
- Surround material: PETP film
- Overall width: 70mm/2.8in
- Overall depth: 50mm/2in
- Fitting: Flange (2 x M6 holes on 76mm, 3.0in PCD)
- Throat exit: 25mm/1.0in
- Unit weight: 0.5kg/1.1lb



XL2213336 Celestion CDX1-1070 T5916 8R 460 kr inklusive moms

Lagerstatus: Ungefär 5 dagar