

Produktblad sE Electronics DM1

sE Electronics DM1 Aktiv förförstärkare för dynamiska och bandmikrofoner, levererar hela +28dB ren och klar signal - Mono.



LOT of gain Some mics need a LOT of gain - and not all preamps are up to the challenge. The DM1

DYNAMITE is an ultra-slim active inline preamp that fits seamlessly between your mic and mic pre, providing a massive +28dB of clean, transparent gain for all your dynamic and passive ribbon microphones - perfect for podcasting, recording, or live sound. With a sophisticated class-A design and specially-selected high-grade FETs, the DM1 has vastly lower output impedance and nearly half the noise of anything else on the market.

Additionally, the gain it provides is always a consistent +28dB regardless of the connected load, thanks to its dedicated buffer amplifier. +28dB OF CLEAN,

CONSISTENT GAIN, INDEPENDENT OF LOAD

designed for neutral, balanced sound quality the

perfect way to boost the signal of a passive microphone gain stays consistent regardless of connected load

provides significantly improved level to your mic preamp for proper gain staging SOPHISTICATED

CLASS-A ELECTRONICS state of the art

electronics and high-grade FETs provide supremely low noise transformerless design for pristine sound

quality provides the lowest noise in its class DEDICATED OUTPUT BUFFER AMPLIFIER

provides +28dB output independent of load impedance or cable length extremely low output impedance

drives long cable runs and can reduce susceptibility to RF interference, buzz & hum SLIM, RUGGED ALL-

METAL HOUSING WITH PREMIUM FINISH efficient rejection of any electrical interference and noise

high-quality finish ensures a great look for many years slim design allows for easy placement in the

studio or on stage GOLD-PLATED XLR CONNECTOR for loss-free and reliable signal connection

SPECIFICATIONS Frequency Range: 10 Hz - 120,000 Hz (-0.3 dB) Gain: 28 dB (load 1kOhms)

Max output level (0.5% THD): 8.3 dBV (2.6 V) Output noise level: 9 1/4V (JIS-A) Powering: 48

Volts according to IEC 61938 Electrical impedance: 135 Ohms Recommended load impedance: större än

1k Ohms Current consumption: 3.0 mA Connectivity: 3-pin male/female XLR connector

Dimensions: Diameter: 19 mm Length: 95.5 mm Weight: 80 g

XL1315910 sE Electronics DM1 1195 kr inklusive moms

Lagerstatus: Ungefär 5 dagar