

COLORdash™ Par-Hex 12



Powered by twelve hex-color RGBAW+UV LEDs, the ultra-compact COLORdash™ Par-Hex 12 satisfies the need for bright ultraviolet light without a separate UV fixture. The 12 LEDs project deeply saturated colors, any variation of white, and bold UV, all without multicolored shadows. A split-yoke bracket eliminates the need for floor stands. Power linking with a locking Neutrik® powerCON® power in and out, 3- and 5-pin DMX connectors make the fixture a great addition for tours, broadcast, and live production.

FEATURES

- Intensely bright LED PAR wash fixture for a wide array of lighting applications
- 12 hex-color (RGBAW+UV) LED chips for ultimate color mixing
- Simple and complex DMX channel profiles for programming versatility
- Four distinct dimming modes for easy incandescent replacement
- Lightweight for easy installation
- Silent, flicker-free operation
- Neutrik® powerCON® power input/output connections

SPECIFICATIONS

- | | |
|--|---|
| • DMX Channels: | 3, 6, 8, 12 or 13 |
| • Data Connectors: | 3- and 5-pin XLR |
| • Light Source: | 12 LEDs (hex-color RGBAW+UV)
10 W, (2.3 A), 50,000 hours life expectancy |
| • Built-in Automated Programs: | Yes |
| • Customizable Programs: | No |
| • Recall Custom Programs: | No |
| • Accessory Holder/
Gel Frame Size: | 9.5 in (241 mm) |
| • Shutter/Strobe: | Electronic |
| • Strobe Rate: | 0 to 20 Hz |
| • Stand-Alone Color Mixing: | Yes |
| • Color Temperature Presets: | No |
| • Installed Optics: | 25° |
| • Beam Angle: | 20° |
| • Field Angle: | 30° |
| • Dimming Modes: | 4 |
| • Illuminance: | 927 lux @ 5 m |
| • Color Temperature (range): | 2800 to 10000 K |
| • IP Rating: | IP20, dry location |
| • Cable Length: | 5 ft (1.5 m) |
| • Power Connection: | Edison plug to Neutrik® powerCON® |
| • Power Input: | Neutrik® powerCON® |
| • Power Output: | Neutrik® powerCON® |
| • Power Linking: | 17 units @ 120 V; 27 units @ 208 V; 30 units @ 230 V |
| • Input Voltage: | 100 to 240 VAC, 50/60 Hz (auto-ranging) |
| • Power and Current: | 96 W, 0.80 A @ 120 V, 60 Hz |
| • Power and Current: | 95 W, 0.49 A @ 208 V, 60 Hz |
| • Power and Current: | 95 W, 0.44 A @ 230 V, 50 Hz |
| • Weight: | 10 lb (4.54 kg) |
| • Dimensions: | 4.41 x 11.73 x 12.72 in (112 x 298 x 323 mm) |
| • Approvals: | CE, MET |