
## **ILUMINARC®**

### COLORIST Pod 7Qa

Item Number: 03630839



#### **LIGHT SOURCE & OPTICAL SPECIFICATIONS**

-191mm [7.53in]

Light Source: 7 LEDs (quad color RGBA) 15 W, (985 mA)

Light Source Lifespan: 50,000 hours based on LED manufacturer's specifications

Installed Optics: 15° Beam Angle: 16° Field Angle: 27° Lumens: 1,176

Base Illuminance: 880 lux @ 5 m

Efficacy: 22.9 lm/W

Minimum Distance to Illuminated Surface: 4 in (92 mm)

### **CONSTRUCTION & PHYSICAL SPECIFICATIONS**

Length: 10.2 in [260 mm] Width: 5.1 in [130 mm] Height: 10.4 in [265 mm] Weight: 10.8 lb [4.9 kg]

Color: Off white

Ingress Protection Rating: IP65 Housing Material: Cast aluminum Lens Cover: Impact resistant glass

Installation Orientation: Installation Orientation: Fixture aperture vertical up +/- 170°

#### **CONTROL SPECIFICATIONS**

Control Protocol: USITT DMX-512a Control Channels: 4, 6 or 10 Stand Alone Control: Yes

Data Connection: 6.6 ft (2 m) Waterproof Cable

Project:			
1 1 0jccu			 



#### **ELECTRICAL SYSTEM SPECIFICATIONS**

Input Voltage: Auto-ranging 100 to 240 VAC,  $50/60\ Hz$ 

Power and Current:

Client:

52 W, .44 A @ 120 V 51 W, .24 A @ 230 V

Power Supply: Electronic internal

Dimmer: Electronic

Power Linking: 23 units @ 120 V, 38 units @ 208 V, 42 units @ 230 V Power Connection: 6.6 ft (2 m) Waterproof cable, Edison plug to proprietary

IP66 input power cord

#### THERMAL SPECIFICATIONS

Cooling: Convection

Startup Temperature Range: -4 °F to 104 °F (-20 to 40) °C Operating Temperature Range: -20 °F to 110 °F (-29 to 43) °C

#### **REGULATORY & VOLUNTARY QUALIFICATION**

Certification Listings: MET, CE

Environment: Wet location, IP65, All indoor and limited outdoor permanent installations. Please refer to the User Manual and/or the Quick

Reference Guide.

Warranty: 24 month manufacturer's limited warranty (for covered regions only)

Product Web Page



# **ILUMINARC®**


COLORIST Pod 7Qa

Item Number: 03630839

Client:_	 	

Project:

Date:\_\_\_\_\_Type:\_\_\_\_



## Typical Installation

