

## ► Features

- 19" Power distribution units
- 8 x German (Type F - CEE 7/4) power outlet
- Male Schuko (CEE 7/7) input connection
- Black aluminium housing
- 1.8 meter cable
- Chassis earth connection point
- 16A ~ 250 VAC / 4000 W Max
- Available with & without illuminated switch
- Rotatable 19" mounting ears

## ► Types

- PSR108G: 8 x Type F (CEE 7/4) power outlet without switch
- PSR108GS: 8 x Type F (CEE 7/4) power outlet with front switch
- PSR118GS: 8 x Type F (CEE 7/4) power outlet with rear switch



## ► Description

The PSR1X8GX are 19" power distribution units, compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. They come in three different models, without switch (PSR108G), with illuminated switch on the socket side (PSR108GS) or with illuminated switch on opposite of socket side (PSR118GS). The construction is made using black powder coated aluminum fitted with steel 19" mounting ears on each side. The total height covers a single 19" rackspace, allowing it to be installed in any 19" housing or equipment rack. Using the rotatable side ears, wall mounting is also made possible. Input connections are made using a fixed 1.8 meter connection cable fitted with a male schuko (CEE 7/7) plug, while german (Type F - CEE 7/4) output sockets allows power distribution to eight devices. A chassis earth connection point is provided for easily connecting your rack / enclosure to mains earth, as required by safety regulations.

## ► Specifications

ARTICLE	Switch	Dimensions (H x W x D)	Weight	Cable length	Unit Height	Power handling
PSR108G	n/a	480 x 45,2 x 44,9 mm	0,82 kg	1,8 m	1 HE	250V AC ~ 16 A / 4000 W
PSR108GS	Yes (Socket side)	480 x 45,2 x 44,9 mm	0,82 kg	1,8 m	1 HE	250V AC ~ 16 A / 4000 W
PSR118GS	Yes (Opposite side)	480 x 45,2 x 44,9 mm	0,82 kg	1,8 m	1 HE	250V AC ~ 16 A / 4000 W