

► Features




- Stores up to 6 units of 19" equipment
- Floor standing & wall mounted use
- Solid constructed (2.5 mm steel - 160 kg load capacity)
- Punched square holes for use with snap-in cage nuts
- Unrestricted air flow due to open-frame design
- Stand alone & in-furniture integration
- Assembly in record-breaking time by a single person (10 min)
- Ships as flat-down package

► Description

The OPR406 is a professional and solid constructed open-frame rack for 19" equipment compliant to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards which is suitable for wall mounted or floor standing installation. It ensures maximum installation, connectivity and maintenance ease storing up to 6 units of 19" equipment. The rugged construction made of 2.5 mm thick steel allows pre-loading of the equipment before transportation to the installation site. Finishing is done in a black (RAL9004) powder coating with fine structure while punched equipment mounting profiles on front and both sides offer a multifunctional use of the cabinet. Delivered in a flat-down package, the simple structure allows assembly by a single person in a record-breaking time.



► Technical Drawing



► Specifications

PROPERTY	VALUE
Unit height	6 HE
Max usable depth	450 mm
Max load standing	160 kg
Max load hanging	80 Kg
Width	518 mm
Depth	450 mm
Height	290,7 mm (excl leveling feet)
Weight	6,65 kg
Rack color	Black (RAL 9004)

► Included Accessories

ARTICLE	QUANTITY
Assembly hardware	1 set
Leveling feet	4
M8 expanding wall bolt	4
Cage nuts + screws	24

► Optional Accessories

ARTICLE	DESCRIPTION
KM600A	Cage nuts
KS600	Screws for cage nuts

► Architects' and Engineers' Specifications

The rack shall be a 19" open frame rack type suitable for wall mounted and floor standing use which complies to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards with 6 usable rackspaces. It shall have the following dimensions: height 290,7 mm, width 518 mm and depth 450 mm with a weight of 6,65 kg

The frame of the rack shall be constructed out of cold rolled steel with a thickness of 2.5 mm, while punched square holes for use with snap-in cage nuts shall be provided for fixation of the equipment. The finishing shall be done in a textured black powder coating (RAL9004) color and have printed unit measurement indicators.

The rack shall ship unassembled as a flat-down package and provide a static load capacity of 160 kg. Fixation points for wall mounted use including expanding wall bolts and leveling feet for floor standing use shall be included.